

# SturdyView™ 21

**21.3 Inch High Resolution Ruggedized Active Matrix TFT LCD Monitor, Designed to Meet Military Specifications. DVI and RGBHV Input. LED Backlight Source and Very High Contrast Ratio.**




## Features

- 21.3" AM LCD
- 1600 x 1200 resolution
- Very high contrast ratio
- Shock resistant
- Vibration resistant
- Meets MIL-STD-810 military standard for environmental specifications

## Applications

- Military vehicles
- Ships
- Submarines
- Aircraft (up to 10,000 feet)
- Industrial use – factories, labs, etc.

## Monitor Dimensions



## Overview

The SturdyView 21 is a 21.3 inch color LCD display, ruggedized for military and industrial use. The SturdyView 21 features an LED light source to deliver rich color reproduction, plus a high contrast ratio for excellent video quality.

The SturdyView 21 is tough enough to be used in all types of moving vehicles.

## Specifications

<b>Panel Type</b>	LCD Active Matrix (AMLCD)
<b>Diagonal Measurement</b>	21.3 inch / 540 mm
<b>Pixel Dimensions</b>	0.27 x 0.27 mm
<b>Color Filter Arrangement</b>	Vertical Stripe RGB Configuration
<b>Image Dimensions</b>	432 x 324 mm
<b>Screen Specification</b>	16, 7M (True 8-bit) color
<b>Brightness</b>	250 cd/m <sup>2</sup>
<b>Contrast Ratio</b>	>400:1 @ dark ambient
<b>Viewing Angle</b>	Horizontal and Vertical: 80/80, 80/80
<b>Input</b>	Standard Analog UXGA / DVI
<b>Resolution</b>	1600 x 1200, 60 Hz
<b>Sync. Pattern</b>	Sync on Green, Separate H & V
<b>Key</b>	Source, Menu, Up, Down, Power
<b>Communication</b>	RS-232, 115200 bps
<b>BIT</b>	Built-in Test Pattern
<b>OSD</b>	On-Screen Display
<b>Power Supply</b>	220VAC / 28VDC option
<b>Mounting</b>	Overall depth behind bezel: 100 mm
<b>Weight</b>	39.7 lbs. (18 Kg)
<b>Cooling</b>	Natural convection
<b>Operating Temp.</b>	-32 ~ 50 °C (MIL-STD-810)
<b>Storage Temp.</b>	-40 ~ 70 °C (MIL-STD-810)
<b>Humidity 95% RH</b>	(MIL-STD-810)
<b>Vibration</b>	MIL-STD-167-1/MIL-E-5400T
<b>Shock</b>	30g - 12.5ms half sine
<b>Altitude</b>	10,000 feet
<b>EMI/EMC</b>	MIL-STD-461E (Optional)
<b>MTBF</b>	20,000 Hrs (backlight module not incl.)

## Ordering Information

- SturdyView 21
- SturdyView 21 with optional 28 Volts DC power supply
- SturdyView 21 with EMI/EMC military standards option

© 2010 Computer Modules, Inc. DVEO and SturdyView are trademarks of Computer Modules, Inc. All other trademarks and registered trademarks are the properties of their respective owners. All rights reserved. Specifications are subject to change without notice.



**Computer Modules, Inc.**

**11409 West Bernardo Court**

**San Diego, CA 92127**

**Tel: (858) 613-1818 Fax: 858-613-1815**

[www.dveo.com](http://www.dveo.com)